

Guanti di protezione per motosega

L'Organismo notificato, Numero di identificazione 0403, ha esaminato questo prodotto tipo, conformemente alla Direttiva 89/686/EEC e successive emendamenti

Riferimento: Chain 402, style 2SA4



EN 381-7:1999

EN 388:2003

Class 1 - 20m/s Design A

3 1 3 2

Istruzioni per l'uso e guida informativa

Attrezzatura per la protezione personale; per garantire la massima protezione e comodità, leggere attentamente le presenti istruzioni.

- **Attenzione!** Questo prodotto non garantisce il corretto funzionamento della motosega né una protezione totale
- Leggere attentamente le norme di sicurezza applicabili alla motosega
- Il guanto deve essere gettato e non utilizzato nel caso in cui l'area protettiva sul lato sinistro o centrale sia stata
 - ❖ danneggiata
 - ❖ lavata o pulita in modo errato
 - ❖ abbia perso la forma originale
- Per prevenire danni al materiale protettivo, eventuali danni al materiale esterno devono essere riparati immediatamente.
- In sede di riparazioni al materiale esterno, prestare attenzione a non penetrare nel materiale protettivo riducendone la capacità protettiva.
- In sede di riparazioni al materiale esterno, non utilizzare adesivi poiché possono deteriorare il materiale protettivo riducendone la capacità protettiva
- Tenere presente che guanti bagnati offrono una minore presa
- Guanto protettivo per motosega, design A conformi alle norme: EN 388 2003, EN 420 2003 EN 381-7 2003
- Simboli per la cura del articolo



Taglia: Per garantire la massima presa durante l'utilizzo della motosega, scegliere la taglia di guanto più appropriata

Taglia	Circonferenza della mano	Lunghezza della mano (punta della dita-polso, polsino escluso)
08	203 mm	182 mm
09	229 mm	192 mm
10	254 mm	204 mm
11	279 mm	215 mm
12	304 mm	226 mm

Per maggiori informazioni:

Certificate No 15205RC501
 Notified Body No 0403
 FI-00250 HELSINKI
 FINLAND

Chainsaw protective gloves

The authorised authority with identification number 0403 has subjected this product to sample testing in accordance with guideline 89/686/EEC:

Reference: Chain 402, style 2SA4



EN 381-7:1999

EN 388:2003

Class 1 - 20m/s Design A

3 1 3 2

General information and instructions for use

Personal protective equipment. To ensure the best possible protection and wearing comfort, please read these instructions for use carefully.

- Warning! This product is no substitute for the careful and proper handling of the chain saw and does not offer complete protection.
- Please read all of the safety regulations relating to your chain saw in detail.
- Gloves should be discarded and no longer used when the surface of the glove or mitt
 - ❖ is damaged
 - ❖ has been incorrectly washed or cleaned
 - ❖ is no longer in its original condition for other reasons.
- Damaged exteriors must be mended immediately to prevent damage to the protective material.
- When mending a damaged surface, ensure that the surface is now sewn into the protective layer as this could be detrimental to the protective properties.
- Do not use adhesives to mend surfaces as this could affect the protective material and be detrimental to the protective properties.
- Please note that moisture can affect the grip of the gloves.
- The protective gloves for chain saws (design A) meet the following standards: EN 388-2003, EN420-2003, EN 381-7:1999.
- Care symbols



Size: To guarantee a secure grip when working with the chain saw, ensure that the gloves/mitt are of the appropriate size.

Size	For hand circumference	Hand length (finger tip to wrist, excl. cuff)
08	203 mm	182 mm
09	229 mm	192 mm
10	254 mm	204 mm
11	279 mm	215 mm
12	304 mm	226 mm

Further information from:

Certificate No 15205RC501
 Notified Body No 0403
 FI-00250 HELSINKI
 FINLAND